

11/07/00

A

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.

97-1165

Total Pages in this Submission

50

**TO THE ASSISTANT COMMISSIONER FOR PATENTS**

Box Patent Application

Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

**PBR WITH TECH BYPASS AND WET DISCONNECT/CONNECT FEATURE**

and invented by:

David Cameron	Lindley Baugh
Russell Miller	Rustom Mody
Robert Smith	Robert Coon
Walter Myron	Michael Carmody

If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Enclosed are:

**Application Elements**

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 14 pages and including the following:
  - a. ☒ Descriptive Title of the Invention
  - b. ☒ Cross References to Related Applications (if applicable)
  - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
  - d. ☐ Reference to Microfiche Appendix (if applicable)
  - e. ☒ Background of the Invention
  - f. ☒ Brief Summary of the Invention
  - g. ☒ Brief Description of the Drawings (if drawings filed)
  - h. ☒ Detailed Description
  - i. ☒ Claim(s) as Classified Below
  - j. ☒ Abstract of the Disclosure

11/06/00

JCS95 U.S. PTO

**UTILITY PATENT APPLICATION TRANSMITTAL  
(Large Entity)***(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.  
**97-1165**Total Pages in this Submission  
**50****Application Elements (Continued)**

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☐ Formal                      Number of Sheets \_\_\_\_\_
- b. ☒ Informal                      Number of Sheets 19
4. ☐ Oath or Declaration
- a. ☐ Newly executed *(original or copy)*                      ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☐ With Power of Attorney                      ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application,  
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied  
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby  
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

**Accompanying Application Parts**

8. ☐ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☒ Information Disclosure Statement/PTO-1449                      ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class    ☒ Express Mail *(Specify Label No.):* EL564088817US

*(Only for new nonprovisional applications<sup>1</sup> under §7 CFR 1.53(b))*

Total Pages in this Submission  
**50**

17. ☐ Pursuant to 35 U.S.C. 122(b)(2), Applicant hereby requests that this patent application not be published pursuant to 35 U.S.C. 122(b)(1). Applicant hereby certifies that the invention disclosed in this application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication of applications 18 months after filing of the application.

***An applicant who makes a request not to publish, but who subsequently files in a foreign country or under a multilateral international agreement specified in 35 U.S.C. 122(b)(2)(B)(i), must notify the Director of such filing not later than 45 days after the date of the filing of such foreign or international application. A failure of the applicant to provide such notice within the prescribed period shall result in the application being regarded as abandoned, unless it is shown to the satisfaction of the Director that the delay in submitting the notice was unintentional.***

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
97-1165

Total Pages in this Submission  
50

**Fee Calculation and Transmittal**

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	68	- 20 =	48	x \$18.00	\$864.00
Indep. Claims	7	- 3 =	4	x \$80.00	\$320.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$710.00
OTHER FEE (specify purpose)					\$0.00
TOTAL FILING FEE					\$1,894.00

- ☐ A check in the amount of \_\_\_\_\_ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 02-0429 as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of \$1,894.00 as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: November 6, 2000

Keith J. Murphy  
Registration No. 33,979



**23413**

CC:

PATENT TRADEMARK OFFICE



Express Mail Label #EL564088817US

PBR WITH TEC BYPASS AND WET DISCONNECT/CONNECT FEATURE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application Serial No. 60/163,575 filed November 5, 1999, which is incorporated herein by reference.

5 BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to downhole electrical connections made up in a wet environment. More particularly, the invention relates to downhole sealed connectors which self-clean upon makeup to avoid contamination in the connection.

10

Prior Art

Downhole power/signal wire connection/disconnection has always been a problem for the industry. More specifically, because the downhole environment is extremely hostile to electric connection (salt water, fresh water, acids, etc.), it has traditionally been thought that a reliable "wet connection" could not be effected. Prior art systems have attempted to create wet connection that employ in the downhole environment but have met with only limited reliability. The prior art connectors are quite small and require an unlikely degree of precision when the connection is to be made, for example, 5000 feet below the surface. Therefore, although these connectors are reasonably capable of providing a good electrical connection at the surface in modern wellbore systems, they fail to solve the need for connection of an uphole string to a downhole string far below the surface. Such connections are required for the plurality of tools incorporated which require power and instructions.

25

SUMMARY OF THE INVENTION

The above-discussed and other drawbacks and deficiencies of the prior art are

overcome or alleviated by the wet connector/disconnector embodiments of the invention.

All of the embodiments of the invention avoid the need to stab-in a small connector. The stabbing-in of the tubing itself is all that is necessary to make up the connection. This is a substantial benefit to the art in view of the growing use of electrically activated downhole tools. The wet connect/disconnect ensures reliability of such systems due to an increase in the likelihood of connection and a reduction in the care needed to effect the connection.

Most of the embodiments disclosed herein employ an insulator that protects a conductor installed with the downhole equipment. The insulator may be rubber, plastic, metal, a grease, etc. with the joining principal being to maintain the conductor in a very clean condition. Additionally, some of the embodiments further include a hydraulic fluid wash to ensure the conductor does not become contaminated when the insulator is pierced or otherwise removed by the string/connector being stabbed in. Generally, the conductor on the stab-in tool is also protected by one or more of the insulators noted above.

Other embodiments do not employ conductor insulators on the downhole string but rely upon a cleansing action of the uphole string upon stab-in to remove any debris or oxidation that may have accumulated on the downhole conductors.

With each of the embodiments disclosed herein, the process of stabbing in causes certain events to occur which lead to secure reliable connections.

In addition to the ability to wet connect, some of the embodiments herein allow for a wet disconnect and reconnect which is advantageous for situations requiring such activity. In one embodiment, a portion of the uphole string is left connected to the downhole string. This leaves the connection made during stabbing-in undisturbed. Rather a piece of the uphole section, which itself provides a new insulated conductor (or not insulated) for a subsequent stab-in procedure, is left behind. Thus, in the event that the uphole section of string needs to be pulled, a reconnection may be made at a later time in the same manner as the original conductor mating. In order to be able to leave a section downhole, a switch section must also be employed to break the connection with the upper string. The switch

section must break the connection in a sealed environment to prevent a short circuit upon reconnecting the uphole string.

### BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings wherein like elements are numbered alike in the several FIGURES:

FIGURE 1 is a schematic elevation view of the concept of the invention;

FIGURE 2 is an enlarged view of a specific embodiment for circumscribed portion A of FIGURE 1;

FIGURE 3 is an enlarged view of an alternate specific embodiment for circumscribed portion A;

FIGURES 4A and 4B are a top and bottom portion of an alternate connection apparatus for the circumscribed portion A in FIGURE 1 in a non-connected position;

FIGURES 5A and 5B are a top and bottom portion of the embodiment of FIGURE 4A and 4B in a connected position;

FIGURES 6 A and 6B are disconnected and connected views, respectively of another alternate embodiment for the circumscribed section A in FIGURE 1;

FIGURE 7 is another alternate embodiment for the circumscribed section A in FIGURE 1;

FIGURES 8A and 8B are disconnected and connected views respectively of another alternate embodiment for the circumscribed section A in FIGURE 1;

FIGURES 9A and 9B are an embodiment of the circumscribed area B in FIGURE 1;

FIGURES 10A-C are various positions of an alternate embodiment of the circumscribed section B in FIGURE 1;

FIGURES 11-13 are an elongated quarter-section view of the tool of this embodiment of the invention to illustrate the disassembled condition;

FIGURES 14-17 are together an elongated quarter-section view of another connector tool of the invention;

FIGURE 18 is a cross section view of the portion of the invention illustrated in FIGURE 11 taken along section line 15-15; and

FIGURE 19 is a cross section view of the portion of the invention illustrated in FIGURE 12 taken along section line 16-16.

#### DETAILED DESCRIPTION OF SEVERAL PREFERRED EMBODIMENTS

Referring to FIGURE 1, a schematic illustration provides an understanding of the disclosure in its broadest sense without details on the specific mechanisms of operable models. It will be understood that many different embodiments are possible which are capable of being employed to effect the desired results aforesaid. Each of the FIGURES following FIGURE 1 illustrate small sections of FIGURE 1 to teach one of skill in the art a way of connecting or disconnecting the circumscribed areas A or B of FIGURE 1. It is also to be appreciated that in many instances in this specification reference is made to “electrical” or “electrically”; this terminology is for exemplary purposes only and it is intended that the reader understand that other conductors such as fiber optic conductors and light could also be employed.

The broad concept begins with the manufacture of a connection device capable of being installed in a wellbore in various ways and connected to various other devices. Figure 1 illustrates schematically, a connection device in a wellbore. In Figure 1, a lower (first) section of wellbore has been completed with (or from the stand point of manufacture is completable with) a tool string 12 having one or more electrically actuated or controlled tools which may have sensors, etc. This lower section 12 is for any number of reasons, which are known to those of skill in the art, isolated from an upper (second) section of tubing string 14. For this reason, providing an electrical connection between the upper section 14 and lower section 12 is needed.

As noted above, such connections have been difficult in the prior art because of the harsh downhole environment. This disclosure therefore, provides a system for such connection by excluding the downhole fluids from the section 12 conductors (or cleaning them) and ensuring that contaminants do not become introduced thereto during connection. Lower section 12 includes associated wires (or fibers) 16 (one or more) which are connected at the factory to conductor pads (connector) 18.

Conductor pads 18 are generally embedded in the tubing and will include a seal thereover to prevent contamination. Lower section 12 is run in the hole or otherwise

disposed downhole in this condition and will remain in a sealed condition with respect to the pads 18 until an upper section 14 is run in the hole to make a connection with pads 18. Exactly how the pads are connected is discussed hereunder.

It will be appreciated in the FIGURE 1 illustration that another distinct part is illustrated between lower section 12 and upper section 14. This is reconnect (third) section 20. Reconnect section 20 is optional to operability of the system with respect to the original connection. It should be appreciated from a review of FIGURE 1 that the features of lower section 12 are duplicated in reconnect section 20. Thus, it will be understood that upper section 14 might only contain features sufficient to mate with lower section 12 and avoid reconnect section 20. In a preferred embodiment, however, reconnect section 20 is included. Section 20 provides features that substitute for the second connector with respect to connection to the first connector. The section allows for the original connection to remain intact if the upper section 14 is pulled for some reason. This prevents contamination of the conductor pads 18. By way of explanation, once the conductor pads 18 are freed from the insulation that protects them (in this type of embodiment) by the action of stabbing in the uphole section, they are left unprotected from the elements. With the upper section attached, no environmental fluid can contact the pads. If the upper section is pulled however, the conductors would be subject to attack by wellbore fluids. Reconnecting to these conductor pads would be unlikely to succeed. For this reason reconnect section 20 is employed. Continuing now with the discussion of section 20, the section includes a disconnect for the wires in the upper section 14 so that the termination of electrical continuity caused by the pulling of section 14 does not allow a "live" connection to contact downhole fluids. This is important to prevent damage to downhole electrical tools or destruction of the system upon reconnect. The disconnection area is schematically illustrated by circumscribed area B in FIGURE 1.

Reconnect section 20 is solely provided to create a stacked system capability. More specifically, reconnect section 20 is connected at the factory to the upper section 14 with a shearable or otherwise releasable connection to upper section 14. In the event upper section 14 must be removed from the hole, it leaves in its wake, reconnect section 20 which includes new sealed connector pads 18' and wires 24

which connect to the original stab in connectors 26. A subsequent upper section may then be stabbed into the reconnect section with the same reliability as the original connection the concept of the reconnect section may be employed over and over again as many times as a disconnect and reconnect are necessary. The reconnect sections  
 5 simply continue to stack up as strings are pulled and reconnected.

Turning now to specific mechanisms, circumscribed area A is discussed first and is directed to several embodiments for creating a clean electrical connection with reliability and high confidence. In these FIGURES, only the connection mechanism is illustrated. It is to be understood that the mechanism is part of section 14 or section  
 10 20 as desired. Following the discussion of area A, circumscribed area B is discussed.

Area B is directed to embodiments for breaking the connection with the wires 22 of section 14 when that section is pulled.

Referring to FIGURE 2, a cover 30 illustrated herein as plastic, but which may be rubber or metallic, is positioned in a sealed relationship over conductor 18. Thus,  
 15 while this portion of lower section 12 is exposed to wellbore fluid, the conductor 18 is protected. The connection mechanism which is shown in place after run in but before actuation, includes a bore 34, preferably filled with hydraulic fluid 30 (or similar). A wedge 38 is provided in the bore 34 which is driven like a piston preferably by pressure from a proximate or remote source into contact with electrical connector 40  
 20 connected with wire 44 from the upper section. Electrical connector 40 includes a ramped surface 46 and a punch 48. Ramped surface 46 is complementary to wedge 38 and connector 40 is urged thereby toward seal material 42. Continued urging of connector 40 results in piercing of seal 42. Upon the piercing of seal 42, fluid 36 escapes from bore 34, flooding the area between seal 42 and seal 30. The flooding  
 25 action displaces wellbore fluids and provides a clean dielectric embodiment in which the connection can be made. Continued urging of connector 40 causes the punch 48 to pierce seal 30 and come into electrical contact with conductor pad 18. It should be noted that fluid 36 may preferably be dielectric fluid or a dielectric grease. The grease is preferred due to its viscosity and therefore its tendency to remain around the  
 30 connection.

Referring now to FIGURE 3, an alternate connection mechanism is illustrated.

This mechanism, it will be appreciated, is very similar to the embodiment of FIGURE 2 and merely adds seals 50 which are preferably chevron type seals. For clarity, the other parts of this embodiment, though slightly different in some respects are numbered identically to FIGURE 2. The FIGURE 3 embodiment provides

5 additional, if redundant, assurance of the continued cleanliness of the connection area.

Seals 50 do not allow fluid to pass in either direction whereas seal 50' allows fluid to pass in only the "out" direction relative to the space defined by seals 50, 50'. Thus, the movement of the cleansing fluid 36, which in this embodiment is preferably hydraulic fluid, will sweep all remnants of well fluids out of the connection space and

10 provide a clean connection area.

Referring to FIGURES 4A, 4B and 5A, 5B another alternate embodiment of the invention is illustrated. Because of the relative complexity of the embodiment, it is illustrated in both a nonconnected and connected form, FIGURES 4A, 4B and 5A, 5B, respectively.

15 Referring first to FIGURES 4A and 4B, lower section 12 will provide a reference. This embodiment functions by sliding the upper section, or reconnect section if so equipped, relative to the lower section 12' against spring biased rings which cover the conductor pads. Lower section 12 of this embodiment includes spring 60 based upon land 62 which biases ring 64 to a position where it covers pad

20 18. Section 12' also includes preferably two o-rings 66, which seal against ring 64, and a wiper 68. Section 14', or 20' if so equipped, includes spring 70 which rests on spring stop 72 and biases ring 74 to a position covering conductor pad 76. Ring 74 is sealed over conductor pad 76 by o-rings 78 mounted in ring 74. Conductor pad 76 is preferably spring loaded by springs 80 so that it will be biased against conductor pad

25 18 when so positioned.

An astute reader, skilled in the art, will recognize that there is a volume 82 that likely is contaminated, and that this volume might be problematic to the connection even in view of wiper 68. To eliminate this possibility, the inventors hereof have provided an enclosed hydraulic fluid reservoir 84 which opens via a

30 rupture disk 86 to volume 82. A piston 88 is provided which is operably connected to reservoir 84 and positioned such that the "sliding past" of this embodiment as

discussed above causes piston 88 to move into reservoir 84 increasing pressure therein until rupture disk 86 fails and hydraulic fluid is expelled into volume 82. The hydraulic fluid will displace any wellbore fluids in the volume 82 and render the area clean.

5 In operation, piston 88 lands on ring 64 and expels the hydraulic fluid as discussed. Once piston 88 is fully depressed into the bore of reservoir 84, shoulder 90 begins to urge ring 64 downhole by over coming the bias of spring 60. Next, ring 74 comes into contact with shoulder 92 of section 12' and is urged uphole by overcoming the spring 72 with downhole movement of the upper section or the reconnect section  
10 as the case may be.

Conductor pad 76 is uncovered at the time it reaches wiper 68 and is wiped clean to remove any oxidation that may have developed over time. Continued downhole movement of the uphole section aligns conductor pads 18 and 76 and the connection is complete.

15 FIGURE 5A and 5B illustrate this embodiment in the connected condition to promote understanding of the invention.

Referring now to FIGURES 6A and 6B, yet another alternative mechanism for the circumscribed area A in FIGURE 1 is illustrated. The lower section of the drawing is an alternative configuration of section 12 and thus is identified as 12". The  
20 conductive pads also differ in appearance and thus are designated 18". The upper section 14" (it should be understood that the upper section of the FIGURE could also be the reconnect section) includes a fluid-filled chamber 100 having an exhaust port 102 sealed by a one-way valve 103 and a rupture disk 104. The chamber 100 is sealed at its other end by seal 106. In a preferred arrangement several o-ring seals are  
25 also supplied and are identified by 108. Focusing on the portion of upper section 14" that defines chamber 100, it will be noted that two wipers 110 are provided. One wiper would be effective but two is preferred for redundancy and better cleaning. Contact pads 112 are provided in this area and are protected by fluid 114 in chamber 100.

30 In use, nose 116 of section 12" is urged into seal 106 ultimately rupturing the seal. since o-rings 108 will prevent fluid 114 from escaping around nose 116, the



fluid instead becomes pressurized. As the pressure in chamber 100 increases, burst disk 104 ruptures and fluid 114 is conveyed through the valve 103 to the tubing I.D. Since valve 103 will not permit fluid to pass in the other direction, the connection area in the chamber 100 will remain clean. Continued movement of nose 116 into  
 5 chamber 100 brings pads 18" into wiping contact with wipers 110 where the conductor pads 18" are cleaned of any oxides that have formed thereon. The pads 18" then align with pads 112 and the connection is made as illustrated in FIGURE 6B.

FIGURE 7 is another alternative embodiment relating to circumscribed area A is illustrated. In this embodiment the upper section provides a connector 120 which is  
 10 composed of a low temperature melt metal (obviously, melting temperature must be above well temperature at projected depth). The metal connector 120 is positioned adjacent conductor pad 18 and includes a coil 122 proximate thereto, the proximity being sufficient to melt the connector 120. As in previous embodiments, seals 134, 132 are provided and a reservoir 128 includes fluid 130 actuated by a piston 126 to  
 15 flush the contact area. In this embodiment a surface actuated current or a downhole actuated current melt the connector 120 which then flows into electrical contact with conductor pad 18.

In another alternate embodiment for circumscribed Section A, referring to FIGURES 8A and 8B lower section 12 includes two conductor pads 18. The upper  
 20 section of the drawing which again can be the equivalent of section 14 or section 20 in FIGURE 1 depending upon whether a reconnect option after a pull-out is to be provided, provides a nose 130 with several seals 132 of preferably the chevron type. Attached to nose 130 by a release mechanism, preferably a shear pin 134, is connector wedge 136 which houses a piercing conductor pad 138 in fluid 140 under seal 142.  
 25 Upon downward movement of the upper section of the drawing (14 or 20) a spring 144 is urged against a ring 146 to move the same downhole until it contacts landing 148 of counter wedge 150. Further downward movement causes counter wedge 150 to move downhole behind connector wedge 136 to cause conductor pads 138 to pierce cover 142 and come into contact with conductor pads 18 to complete the circuit.

30 As discussed above, in the event upper section 14 is removed from the hole, the connections must be broken to prevent a short circuit. This is, for illustrative

purposes, at the area marked B on FIGURE 1. It is important to note that just stretching the connectors to break leaves them exposed to wellbore fluids and invites short circuit. Therefore the inventors hereof have provided the following two embodiments of disconnects. It is to be understood, however, that other mechanisms for providing such a disconnect are clearly within the scope of the invention.

Turning now to FIGURES 9A and 9B, the first disconnect embodiment is illustrated in the connected position and the disconnected position. The disconnect itself comprises a connector pad 162 disposed atop an insulator 160 in a recess 172 in section 12. The recess 172 is sealed by cover 168 which may be of a plurality of distinct materials so long as they either deflect or allow a sealed sliding of the pins 166 therethrough. In the case of deflection, the pins 166 need not slide through cover 168 (the non-sliding arrangement being illustrated herein).

As one can readily ascertain from the drawings, pins 166 provide a base for pads 164, the pins extending to outside cover 168 and into connection with plate 170. The disconnect is connected together in the factory and appears as illustrated in FIGURE 9A. When a disconnect is desired, pulling the tool causes the switch to be in the condition illustrated in FIGURE 9B wherein the electrical connection is broken and the ends of the downhole wires are protected within recess 172 and cover 168. It will be apparent to one of skill in the art that if upper portion 174 of the drawings is to be removed altogether the disconnect will have to shear at a point above the cover 168. Alternatively, the portion 174 could simply be a ring which remains downhole.

Referring now to FIGURES 10A, 10B and 10C a second disconnect embodiment is illustrated. This disconnect is intended to work in much the same way that the embodiment of FIGURES 9A 9B works and thus only the distinctions are discussed here. Contact bar 180 is connected to an uphole piece of the pipe and supports actuator pin 182 and contact pins 184. Pin 182 includes a wedge 186 which is angled sufficiently to actuate slide 190 through slide pitch 188. Actuation of slide 190 moves it (to the right in the drawing) to align ports 192 with contact receptacles 194 wherein contact pads 196 are disposed and connected to wires 198. Once alignment as described is complete, pins 184 may come into electrical contact with pads 196 (pads 196 are insulated from the metallic tool by insulation 200).

The length of the pins 182 and 184 is important to the operation of the invention. Upon disconnecting, it is required that the slide 190 be closed (under bias of spring 204) prior to pins 184 pulling free from membrane 202. By so requiring, the breach in the seal of membrane 202 due to the pins 184 being extended therethrough is not able to allow contamination into receptacles 194. Obviously it is intended that slide 190 make sealing contact with the surrounding area. This embodiment is made up in the factory preferably but is also useable in the field because of the ability of pin 182 to actuate slide 190 in a time frame where the pins 184 will protectively be in membrane 202.

In yet another embodiment of the invention wherein conductors are aligned and connected. Referring initially to FIGURES 11-13 a more schematic view of the invention is illustrated. The view does not contain all of the parts of the invention and thus is intended to convey the locations and orientation of the connectors. Tool 10 breaks down to a top half (comprising FIGURES 11 and 12) and a bottom half comprising FIGURE 13. When the halves are separated as illustrated in FIGURES 11-13, lower seal adapters 212 (twelve of them on the embodiment shown although more or fewer could be employed) are visible on bottom half (FIGURE 13) and the complementary upper seal adapters 214 (an equal number to the number of lower seal adapters 212). Upper seal adapters 214 preferably include a pair of o-rings 270 to fluid tightly seal the lower seal adapters. Upper seal adapters 214 are connected to the uphole environment via conduits 218 while at the other end of the connection, lower seal adapters 12 are connected to the downhole environment via conduit 20. The conduits 218 and 220 preferably contain fiber optic conductors. The mating ends of the conductors are cleaned by preferably a hydraulic fluid which may be applied in a number of ways including adaptations of the embodiments preferably does not include threads between the alignment profile and end connections.

Although the top and bottom portions of the tool are run in the hole together (assembled at the surface), an alignment profile 222 is provided in the tool to align the top and bottom halves in the event that they are separated. Therefore, referring directly to FIGURES 12 and 13, a profile 224 is a raised area in a predetermined orientation on the anchor sub 226. The profile 224 mates with a complementary

profile 228 in bottom half (FIGURE 13). The orientation profiles ensure that the lower seal adapters 212 will align and mate with upper seal adapters 214 reliably.

Turning now to the internal components of this embodiment of the invention, referring to FIGURES 14-19, and beginning at the uphole end of the tool, a box thread 230 is provided to attach the tool to a work string (not shown). The box thread 230 is cut in body 232 which extends downhole to threadedly mate with anchor sub 234 at thread 236. Body 232 supports, near the uphole end thereof, disc spring retainer cap 238 which is threaded to the O.D. of body 232 at thread 240. Cap 238 is further preferably anchored by cap screw 242. Cap 238 functions to retain preferably a plurality of disc springs (belleville washers) 244. Springs 244 absorb longitudinal movement of upper and lower seal adapters. Moreover, the washers keep the upper and lower seal adapters positively shouldered internally which is important for pump down, replaceable optic fiber installation and other installations. Disc springs 244 are maintained in position at the downhole end by retainer sub 246. Sub 246 is annular and is threaded to disc spring adjustment sub 248 at thread 250.

Downhole of attachment sub 248 and radially outwardly of body 232 is upper connector 252. Upper connector 252 houses upper seal adapters 214 at the downhole end thereof and a line connector assembly 254 which preferably comprises a pair of ferrules and a jam nut (not individually shown). The connector 252 is retained in position on body 232 by shear screw 256 and shoulder screw 258. These latter screws are best viewed in FIGURE 18. A plurality of bores 260 are provided in upper connector 252 to receive conduit 218. Lower connector 262 (FIGURES 15 and 19) is disposed downhole of upper connector 252 and houses lower seal adapter 212, bore 264 for conduit 220 and a control line connector 260 which comprises a pair of ferrules and a jam nut (not individually shown). It should be noted that FIGURE 15 provides a cross section view of the tool which shows the upper and lower seal adapters that were explained previously herein. It should also be noted that upper seal adapter 214 includes two sets of o-rings 268 and 270. Rings 268 seal upper seal adapter 214 to upper connector 252 while rings 270 seal the lower seal adapter 212 into the upper seal adapter 214 when it is so engaged. Lower adapter 212 may be for

conventional conductors or fiber optic conductors. FIGURE 19 illustrates three of four (212a) in conventional form and one (212b) in fiber optic form .

Bridging FIGURES 15 and 16 is sleeve 272 which covers the components of the snap in/snap out feature of the invention (components discussed hereunder).

5 Sleeve 272 is connected to seal housing 274 which includes locking dogs 276. Seal housing is also threaded at 278 for a body lock ring 280. The lock ring 280 is rotationally arrested by roll pin 236. Seal housing 274 is sealed to anchor sub 234 by seal stack 281.

10 Radially outwardly of seal housing 274 (FIGURES 16 and 17) are housing 282 and control line sub 284. Housing 282 includes several seals 286, several screws 288 and a dog receiving profile 290.

15 Radially inwardly of sleeve 272 (FIGURE 16) is the snap in/snap out assembly mentioned above. The assembly includes, beginning from the uphole end, a shear ring retainer 292 which is connected to the anchor sub 234 by shear ring 294. Shear ring retainer 292 is also connected to support ring 298 through set screws 296 and thread 300. Support ring 298 supports set down sleeve 302 and is in contact with body lock housing 306. Body lock ring housing 306 is connected to body lock ring 304 conventionally and including a set screw 308 to arrest rotational movement. Body lock ring housing 306 is also threadedly connected to set down sleeve 302 by  
20 thread 310. Body lock ring housing 306 cannot move up or downhole because of shear screw 312 which engages anchor sub 234. Body lock ring housing 306 is connected to latch 314 by parting ring 316 which is a ring having holding profiles 318 to retain the body lock ring housing 306 to latch 314 until a predetermined tensile load is placed thereon which breaks the parting ring 316.

25 In operation and after running in the hole, a pressure line 243 (FIGURE 16) pressurizes a piston area 318 sealed by seals 86. Upon reaching a predetermined pressure, shear screw 288 shears and allows housing 282 to move downhole thus locating recess 290 over locking dogs 276 allowing them to move radially outwardly to disengage from anchor sub 234. Once anchor sub 234 is disengaged from the dogs  
30 276 it will be free to move. Body lock ring 280 is provided to prevent housing 282 from moving back uphole and reseating the dogs 276. After initial setting then, the

housing portion of the tool is permanently moved and the dogs 276 are permanently disengaged from anchor sub 234. Following this disengagement, the tool upper portion (FIGURES 11 and 12) and lower portion (FIGURE 13) are separable using the snap in/snap out assembly in order to develop a proper space-out for the particular well, the tool may be snapped in/snapped out as many times as necessary until sufficient weight is committed and the anchor sub 234 supports the latch 314. In this latter condition the snap out feature is disabled.

Once the space out is appropriate, set down weight which exceeds the shear strength of shear ring 294 and shear screw 312 is applied. After shearing, anchor sub 234 moves downhole through lock ring 304 and is retained in this position until retrieval is necessary or desired.

In order to retrieve the tool, a tensile load is placed on the anchor sub which transmits to the body lock ring 304, the parting ring 316 and the latch 314. When a predetermined tensile load is exceeded, the parting ring fails and the anchor sub 34 moves uphole. This unsupports latch 314 allowing the latch to deflect into recess 320 and the snap out sub is operational. Continued tensile load will disengage the upper portion of the tool from the lower portion for retrieval. The process as described can then be repeated with a new or rebuilt upper portion.

While preferred embodiments have been shown and described, various modifications and substitutions may be made thereto without departing from the spirit and scope of the invention. Accordingly, it is to be understood that the present invention has been described by way of illustration and not limitation.

What is claimed is:

CLAIM 1. A conductor connection device for a downhole environment comprising:

a first section connectable to implements intended to be located farther downhole than said first section when said device is installed in a wellbore;

5 at least one first conductor associated with said first section;

a first connector in operable communication with said at least one first conductor, said first connector being maintained in a clean condition or being cleanable by operation of the connection device;

10 a second section connectable to implements intended to be located farther uphole than said second section when said device is installed in a wellbore;

at least one second conductor associated with said second section;

a second connector in operable communication with said at least one second conductor, said second connector being maintained in a clean condition or being cleanable by operation of the connection device, said second connector being  
15 connectable to said first connector by operation of said connection device.

CLAIM 2. A conductor connection device as claimed in claim 1 wherein said connection device further comprises:

a third section connectable to said second section prior to being run downhole to substitute for functions of the second section related to the second connector and

5 releasable from said second section after connection with said first section;

at least one third conductor associated with said third section;

a third connector in operable communication with said at least one third conductor, said third conductor also being in operable communication with said at least one second conductor, said third conductor being maintained in a clean

10 condition or cleanable by operation of said connection device;

said third connector being connectable to said first connector by operation of said connection device;

a forth connector in operable communication with said at least one third conductor, said forth connector being maintained in a clean condition or being

15 cleanable by operation of a subsequently run connection device.

CLAIM 3. A conductor connection device as claimed in claim 1 wherein said first connector and said second connector each comprise:

at least one pad;

at least one fluid impermeable covering on each said at least one pad.

CLAIM 4. A conductor connection device as claimed in claim 3 wherein said connection device further includes at least one interconnector providing interconnection between said first connector pad and said second connector pad.

CLAIM 5. A conductor connection device as claimed in claim 4 wherein said interconnector is a conductive piercing member which pierces said at least one fluid impermeable covering on each said at least one pad upon operation of said connection device.



CLAIM 6. A conductor connection device as claimed in claim 1 wherein said connection device is configured to provide a dielectric material to a vicinity of interconnection between said first connector and said second connector.

CLAIM 7. A conductor connection device as claimed in claim 5 wherein said covering is rubber.

CLAIM 8. A conductor connection device as claimed in claim 5 wherein said covering is metal.

CLAIM 9. A conductor connection device as claimed in claim 6 wherein said dielectric material is oil.

CLAIM 10. A conductor connection device as claimed in claim 6 wherein said dielectric material is grease.

CLAIM 11. A conductor connection device as claimed in claim 1 wherein said first connector and said second connector are exposed to environmental conditions and are wiped clean during operation of the connection device.

CLAIM 12. A conductor connection device as claimed in claim 11 wherein said device is configured to provide a dielectric material to an interconnection vicinity of said connection device.

CLAIM 13. A conductor connection device as claimed in claim 12 wherein said dielectric material is oil.

CLAIM 14. A conductor connection device as claimed in claim 12 wherein said dielectric material is grease.

CLAIM 15. A conductor connection device as claimed in claim 12 wherein said dielectric material is dispensed from a reservoir in said device.

CLAIM 16. A conductor connection device as claimed in claim 11 wherein said first connector and said second connector are wiped clean by each other.

CLAIM 17. A conductor connection device as claimed in claim 11 wherein said first connector and said second connector are wiped clean by a wiper.

CLAIM 18. A conductor connection device as claimed in claim 15 wherein said reservoir includes a check valve.

CLAIM 19. A conductor connection device as claimed in claim 1 wherein said first connector is a pad and said second connector includes a meltable conductive element.

CLAIM 20. A conductor connection device as claimed in claim 19 wherein said element is meltable by a coil.

CLAIM 21. A conductor connection device as claimed in claim 20 wherein said coil is powered from within said device.

CLAIM 22. A conductor connection device as claimed in claim 20 wherein said coil is powered from external to said device.

CLAIM 23. A conductor connection device as claimed in claim 1 wherein said device is configured to provide a dielectric material to an area of interconnection of said first connector and said second connector.

CLAIM 24. A conductor connection device as claimed in claim 23 wherein said dielectric material is oil.

CLAIM 25. A conductor connection device as claimed in claim 23 wherein said dielectric material is grease.

CLAIM 26. A conductor connection device for a downhole environment comprising:

a first section connectable to implements intended to be located farther downhole than said first section when said device is installed in a wellbore;

at least one first conductor associated with said first section;

a first connector in operable communication with said at least one first conductor, said first connectors being maintained in a clean condition or being cleanable by operation of the connection device;

a second section connectable to implements intended to be located farther uphole than any said second section when said second section is installed in a wellbore;

at least one second conductor associated with said second section;

a third section operably connected to said second section ;

at least one third conductor associated with said third section, said at least one third conductor being operably connected to said at least one second conductor;

a third connector in operable communication with said at least one third conductor, said third connector being maintained in a clean condition or being cleanable by operation of the connection device, said third connector being connectable to said first connector by operating said connection device, said third section being separable from said second section after said connection device is operated;

a forth connector in operable communication with said at least one third conductor, said forth connector being maintained in a clean condition or being cleanable by operation of a subsequent connection device.

CLAIM 27. A conductor connection device as claimed in claim 26 wherein said third section further comprises a conductor break to prevent conductive contact of said at least one first conductor through said at least one third conductor with wellbore fluids upon separation of said third section from said second section.

CLAIM 28. A conductor connection device as claimed in claim 27 wherein said conductor break comprises at least two contacts maintained in a clean environment, said contacts being separable upon separation of said second section.

CLAIM 29. A conductor connection device as claimed in claim 28 wherein said clean environment is maintained by a deflectable cover to which one of said at least two contacts is connected, said deflectable cover being deflected to maintain connection of said at least two contacts while said third section is attached to said second section.

CLAIM 30. A conductor connection device as claimed in claim 27 wherein said conductor break comprises:

- at least one contact pin; and
- at least one contact receptacle.

CLAIM 31. A conductor connection device as claimed in claim 30 wherein said break further comprises a slide which seals said at least one receptacle when said at least one pin is not engaged in said at least one receptacle.

CLAIM 32. A conductor connection device as claimed in claim 31 wherein said break further includes an actuator pin to actuate said slide.

CLAIM 33. A conductor connection device as claimed in claim 26 wherein said first connector and said third connector each comprise:

- at least one pad;
- at least one fluid impermeable covering on each said at least one pad.

CLAIM 34. A conductor connection device as claimed in claim 33 wherein said connection device further includes at least one interconnector providing interconnection between said first connector pad and said third connector pad.

CLAIM 35. A conductor connection device as claimed in claim 34 wherein said interconnector is a conductive piercing member which pierces said at least one fluid impermeable covering on each said at least one pad upon operation of said connection device.

CLAIM 36. A conductor connection device as claimed in claim 26 wherein said connection device is configured to provide a dielectric material to a vicinity of interconnection between said first connector and said third connector.

CLAIM 37. A conductor connection device as claimed in claim 35 wherein said covering is rubber.

CLAIM 38. A conductor connection device as claimed in claim 35 wherein said covering is metal.

CLAIM 39. A conductor connection device as claimed in claim 36 wherein said dielectric material is oil.

CLAIM 40. A conductor connection device as claimed in claim 36 wherein said dielectric material is grease.

CLAIM 41. A conductor connection device as claimed in claim 26 wherein said first connector and said third connector are exposed to environmental conditions and are wiped clean during operation of the connection device.

CLAIM 42. A conductor connection device as claimed in claim 41 wherein said device is configured to provide a dielectric material to an interconnection vicinity of said connection device.

CLAIM 43. A conductor connection device as claimed in claim 42 wherein said dielectric material is oil.

CLAIM 44. A conductor connection device as claimed in claim 42 wherein said dielectric material is grease.

CLAIM 45. A conductor connection device as claimed in claim 42 wherein said dielectric material is dispensed from a reservoir in said device.

CLAIM 46. A conductor connection device as claimed in claim 41 wherein said first connector and said third connector are wiped clean by each other.

CLAIM 47. A conductor connection device as claimed in claim 41 wherein said first connector and said third connector are wiped clean by a wiper.

CLAIM 48. A conductor connection device as claimed in claim 45 wherein said reservoir includes a check valve.

CLAIM 49. A conductor connection device as claimed in claim 26 wherein said first connector is a pad and said third connector includes a meltable conductive element.

CLAIM 50. A conductor connection device as claimed in claim 49 wherein said element is meltable by a coil.

CLAIM 51. A conductor connection device as claimed in claim 50 wherein said coil is powered from within said device.

CLAIM 52. A conductor connection device as claimed in claim 50 wherein said coil is powered from external to said device

CLAIM 53. A conductor connection device as claimed in claim 26 wherein said device is configured to provide a dielectric material to an area of interconnection of said first connector and said third connector.

CLAIM 54. A conductor connection device as claimed in claim 53 wherein said dielectric material is oil.

CLAIM 55. A conductor connection device as claimed in claim 53 wherein said dielectric material is grease.

CLAIM 56. A downhole connection device comprising:

at least two connectors on an uphole end of a connection interface;

at least two complementary connectors on a downhole end of said connection interface; and

a self orienting profile within said connection device.

CLAIM 57. A downhole conductor connection device comprising:

a downhole portion including a lower conductor leading farther downhole and an orientation profile;

an uphole portion having a conductor leading farther uphole and a complementary orientation profile;

at least one lower seal adapter connected to said lower conductor; and

at least one upper seal adapter connected to said upper conductor, said lower seal adapter being receivable in said upper seal adapter to connect said lower conductor to said upper conductor.

CLAIM 58. A downhole conductor connection device as claimed in claim 57 wherein said connection device further includes a snap in/snap out thread.

CLAIM 59. A downhole conductor connection device as claimed in claim 57 wherein said device further comprises a dog support system to lock said device in a selected position.

CLAIM 60. A downhole conductor connection device as claimed in claim 59 wherein said dog support system is collapsible upon pressuring a control line to shift a housing.

CLAIM 61. A method for downhole conductor connection comprising:

running a downhole and an uphole connector portion in a sealed engaged condition;

opening said sealed engaged connector;

orientating said uphole connector with said downhole connector; and

reengaging at least one conductor.

CLAIM 62. A method for creating a conductive connection in a downhole environment comprising:

installing a first section connectable to implements located farther downhole from an intended location of said first section, said first section having at least one conductor associated therewith and a connector operably connected to said at least one conductor, said conductor being maintained in a clean condition or being cleanable upon engagement of said first section with a second section;

installing said second section connectable to implements located further uphole than an intended location of said second section, said second section having at least one conductor associated therewith and a connector operably connected to said at least one conductor, said conductor being maintained in a clean condition or being cleanable upon engagement of said first section with said second section, engaging said first section with said second section.



15

CLAIM 63. A method for creating a conductive connection as claimed in claim 62 wherein said engaging includes forming a conductive connection between said first section and said second section.

CLAIM 64. A method for creating a conductive connection as claimed in claim 62 wherein said engaging causes self orientation of said first section and said second section.

CLAIM 65. A method for creating a conductive connection in a downhole environment while providing for disconnection and reconnection comprising:

installing a first section connectable to implements located farther downhole than an intended location of said first section, said first section having at least one  
5 conductor associated therewith and a connector operably connected to said at least one conductor;

installing a second section connectable to implements located farther uphole than an intended location of said second section, said second section having at least one conductor associated therewith, said second section further including a third  
10 section having at least one conductor associated therewith and a third connector operably connected at one end to said at least one conductor and a fourth connector operably connected at the other end of said at least one connector; and

engaging said third section and said first section

CLAIM 66. A method for creating a conductive connection as claimed in claim 65 further including:

disconnecting said second section from said third section; and

installing a separate second section and engaging said third section in position  
5 as connected to said first section.

CLAIM 67. A method for creating a conductive connection as claimed in claim 62 wherein said engaging includes flushing with a dielectric fluid, a connection area of interconnection between said first connector and said second connector.

CLAIM 68. A method for creating a conductive connection as claimed in claim 65 wherein said engaging includes flushing with a dielectric fluid, a connection area of interconnection between said first connector and said third connector.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2

### ABSTRACT OF THE INVENTION

A wet connect/disconnect arrangement is disclosed for a downhole system that allows installation of various tools and/or a string and subsequent electrical connection to the downhole system in a wet environment. Several embodiments are disclosed, all of which produce a clean, reliable connection.

00007164 14000




FIG 1




FIG 2






FIG 3


③ A  
UPPER




④ A  
UPPER







4 B  
LOWER



3 B  
LOWER



09707165 410600




FIG 6A  
—A—

7668

- B -




Fig 7






FIG.  
— 8 A —






Fig.  
— 8B —

00001168-110000






FIG 10 A



06707488 14000

09707169-110600





FIG 10 B



000001 000001 000001




196.


Fig 10C

FIG. 11

210



210



224

FIG. 12

218

212

212

228

210

20

210

214




FIG. 13






FIG. 14



SECTION 'A-A'


FIG. 18

191



## SECTION 'B-B'

7.019



53,57,58

FIG. 16

FIG. 17





FIG. 17

United States Patent & Trademark Office  
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☒ Scanned copy is best available. *drawings*

SCANNED, # 14